

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 2

JAN 13 2006

Listing of Claims:

1. (Previously Presented) A method of distributing workload between a plurality of servers, the method comprising:
 - receiving a plurality of requests over a first connection;
 - parsing the plurality of requests to determine application layer information associated with each of the plurality of requests;
 - selecting destination servers for corresponding ones of the plurality of requests based on the determined application layer information associated with each of the plurality of requests; and
 - distributing the plurality of requests to the corresponding selected destination servers over a plurality of second connections associated with respective ones of the destination servers, wherein selecting destination servers for corresponding ones of the plurality of requests comprises:
 - determining if the determined application layer information associated with each of the plurality of requests is relevant application layer information;
 - selecting one of a subset of the destination servers if the application layer information associated with each of the plurality of requests is relevant application layer information; and
 - selecting a destination server other than a destination server in the subset of the destination servers if the application layer information associated with each of the plurality of requests is not relevant application layer information.
2. (Original) A method according to Claim 1, wherein the first connection comprises an HTTP 1.1 connection.
3. (Original) A method according to Claim 1, wherein parsing the plurality of requests comprises:
 - determining a start point and an end point for each of the plurality of requests within the first connection; and
 - identifying application layer information within each of the plurality of requests.

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 3

4. (Original) A method according to Claim 3, wherein the application layer information comprises layer 7 information and above.
5. (Original) A method according to Claim 3, wherein the application layer information comprises at least one of a type of request, a client identification, an individual user identification, and a cookie.
6. (Original) A method of Claim 1, wherein the plurality of requests comprise a plurality of Hypertext Transport Protocol(HTTP) requests.
7. (Cancelled).
8. (Previously Presented) A method of Claim 1, wherein selecting one of a subset of the destination servers if the application layer information associated with each of the plurality of requests is relevant application layer information, further comprises:
determining a load associated with respective destination servers in the subset of destination servers; and
selecting the destination server in the subset of the destination servers based on the determined load.
9. (Previously Presented) A method of Claim 1, wherein the subset of destination servers includes at least one server which is to receive requests having an indication of high priority, and wherein the indication of high priority is determined based on the existence and nonexistence of relevant application layer information.
10. (Original) A method according to Claim 1, wherein distributing the plurality of requests comprises:
determining if a second connection associated with a selected destination servers exists;
establishing the second connection to the selected destination server if the second

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 4

connection does not exist;

distributing a request to the selected destination servers over the second connection; and
repeating the determining, establishing and distributing for each of the plurality of
requests.

11. (Original) A method according to Claim 1, wherein receiving, parsing, selecting and distributing are carried out by an application executing on a data processing system.
12. (Original) A method according to Claim 1, further comprising tracking the plurality of requests and a plurality of corresponding responses to the plurality of requests.
13. (Original) A method according to Claim 1, wherein distributing the plurality of requests, comprises:
routing the plurality of requests using network address translation at a routing layer of a communication protocol stack.
14. (Original) A method according to Claim 13, wherein routing the plurality of requests further comprises routing the plurality of requests using session control translation at the routing layer of the communication protocol stack.
15. (Original) A method according to Claim 14, wherein routing the plurality of requests includes routing the corresponding responses to the plurality of requests using network address translation at a routing layer of a communication protocol stack.
16. (Original) A method of distributing workload between a plurality of servers, wherein each of the plurality of servers is executing an instance of an application which communicates over a network such that each of a plurality of HTTP requests within a single HTTP 1.1 connection to the application may be distributed to any one of the plurality of servers, the method comprising:

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 5

defining a subset of the plurality of servers which are to receive HTTP requests having an indication of high priority;

establishing an HTTP 1.1 connection responsive to receiving a request for an HTTP 1.1 connection to the application over the network;

receiving a first Hypertext Transport Protocol(HTTP) request within the HTTP 1.1 connection;

parsing the first HTTP request to determine if the first HTTP request has an indication of high priority based on application layer information included in the first HTTP request; and

distributing the first HTTP request to one of the subset of the plurality of servers over a first connection if the first HTTP request has an indication of high priority.

17. (Original) A method according to Claim 16, further comprising:
distributing the first HTTP request to a server other than a server in the subset of the destination servers if the first HTTP request does not have an indication of high priority.

18. (Original) The method according to Claim 16, further comprising:
receiving a second HTTP request within the HTTP 1.1 connection
parsing the second HTTP request to determine if the second HTTP request has an indication of high priority based on application layer information included in the second HTTP request;

distributing the second HTTP request to one of the subset of the plurality of servers over a second connection if the second HTTP request has an indication of high priority;
and

repeating the receiving, parsing and distributing steps for each subsequent HTTP request received within the HTTP 1.1 connection.

19. (Original) A method according to Claim 16, wherein distributing the first HTTP request, further comprises:

determining a load associated with respective servers in the subset of the plurality of

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 6

servers; and

distributing the first HTTP request to the server in the subset of the plurality of servers based on the determined load.

20. (Original) A method according to Claim 16, wherein the indication of high priority is based on the existence and nonexistence of relevant application layer information.

21. (Original) A method according to Claim 20, wherein the application layer information comprises at least one of a type of request, a client identification, an individual user identification, and a cookie.

22. (Original) A method according to Claim 20, wherein the application layer information comprises layer 7 information and above.

23. (Original) A method according to Claim 16, wherein parsing the first HTTP request comprises:

- determining a start point and an end point for the first HTTP request within the HTTP 1.1 connection;
- identifying application layer information within the first HTTP request; and
- determining if the application layer information is relevant application layer information.

24. (Original) A method according to Claim 16, wherein distributing the first HTTP request comprises:

- determining if a first connection exists;
- establishing the first connection if the first connection does not exist; and
- distributing the first HTTP request over the first connection.

25. (Original) A method according to Claim 16, wherein the steps of defining, receiving, parsing, and distributing are carried out by an application executing on a data processing system.

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 7

26. (Original) A method according to Claim 16, further comprising tracking the HTTP request and a corresponding response to the HTTP request.

27. (Original) A method according to Claim 16, wherein distributing the first HTTP request comprises:

routing the first HTTP request using network address translation at a routing layer at a communication protocol stack.

28. (Original) A method according to Claim 27, wherein routing the first HTTP request further comprises routing the first HTTP request using session control translation at the routing layer at the communication protocol stack.

29. (Original) A method according to Claim 28, wherein routing the first HTTP request includes routing the corresponding response to the first HTTP request using network address translation at a routing layer of a communication protocol stack.

30. (Previously Presented) A system for distributing workload between a plurality of servers, comprising:

means for receiving a plurality of requests over a first connection;

means for parsing the plurality of requests to determine application layer information associated with each of the plurality of requests;

means for selecting destination servers for corresponding ones of the plurality of requests based on the determined application layer information associated with each of the plurality of requests; and

means for distributing the plurality of requests to the corresponding selected destination servers over a plurality of second connections associated with respective ones of the destination servers, wherein the means for selecting destination servers for corresponding ones of the plurality of requests comprises:

means for determining if the determined application layer information associated

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 8

with each of the plurality of requests is relevant application layer information;

means for selecting one of a subset of the destination servers if the application layer information associated with each of the plurality of requests is relevant application layer information; and

means for selecting a destination server other than a destination server in the subset of the destination servers if the application layer information associated with each of the plurality of requests is not relevant application layer information.

31. (Original) A system for distributing workload between a plurality of servers, wherein each of the plurality of servers is executing an instance of an application which communicates over a network such that each of a plurality of HTTP requests within a single HTTP 1.1 connection to the application may be distributed to any one of the plurality of servers, comprising:

means for defining a subset of the plurality of servers which are to receive HTTP requests having an indication of high priority;

means for establishing an HTTP 1.1 connection responsive to receiving a request for an HTTP 1.1 connection to the application over the network;

means for receiving a first Hypertext Transport Protocol(HTTP) request within the HTTP 1.1 connection;

means for parsing the first HTTP request to determine if the first HTTP request has an indication of high priority based on application layer information included in the first HTTP request; and

means for distributing the first HTTP request to one of the subset of the plurality of servers over a first connection if the first HTTP request has an indication of high priority.

32. (Previously Presented) A computer program product for distributing workload between a plurality of servers, comprising:

a computer readable program medium having computer readable program code embodied therein, the computer readable program code comprising:

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 9

computer readable program code which receives a plurality of requests over a first connection;

computer readable program code which parses the plurality of requests to determine application layer information associated with each of the plurality of requests;

computer readable program code which selects destination servers for corresponding ones of the plurality of requests based on the determined application layer information associated with each of the plurality of requests; and

computer readable program code which distributes the plurality of requests to the corresponding selected destination servers over a plurality of second connections associated with respective ones of the destination servers, wherein the computer readable program code configured to select destination servers for corresponding ones of the plurality of requests comprises:

computer readable program code configured to determine if the determined application layer information associated with each of the plurality of requests is relevant application layer information;

computer readable program code configured to select one of a subset of the destination servers if the application layer information associated with each of the plurality of requests is relevant application layer information; and

computer readable program code configured to select a destination server other than a destination server in the subset of the destination servers if the application layer information associated with each of the plurality of requests is not relevant application layer information.

33. (Original) A computer program product for distributing workload between a plurality of servers, wherein each of the plurality of servers is executing an instance of an application which communicates over a network such that each of a plurality of HTTP requests within a single HTTP 1.1 connection to the application may be distributed to any one of the plurality of servers, comprising:

a computer readable program medium having computer readable program code embodied therein, the computer readable program code comprising:

Attorney Docket No. 5577-230
Application Serial No. 09/833,925
Filed: April 12, 2001
Page 10

computer readable program code which defines a subset of the plurality of servers which are to receive HTTP requests having an indication of high priority;

computer readable program code which establishes an HTTP 1.1 connection responsive to receiving a request for an HTTP 1.1 connection to the application over the network;

computer readable program code which receives a first Hypertext Transport Protocol(HTTP) request within the HTTP 1.1 connection;

computer readable program code which parses the first HTTP request to determine if the first HTTP request has an indication of high priority based on application layer information included in the first HTTP request; and

computer readable program code which distributes the first HTTP request to one of the subset of the plurality of servers over a first connection if the first HTTP request has an indication of high priority.